

40V 0.8mohm N-channel SGT MOSFET
AKG4N008GM-A

Description:

This device is designed for automotive applications and manufactured in IATF16949 certified facilities. Qualified AEC-Q101, PPAP capable.

Features:



- Low $R_{DS(ON)}$
- 100% UIS Tested
- RoHS compliant ^(Note 1)
- Halogen-free ^(Note 1)
- AEC-Q101 qualified and PPAP capable

Applications:

- Battery Management System
- Motor Drivers

Key Performance Parameters:

Parameter	Value	Unit
V_{DS}	40	V
$R_{DS(ON)}$, max @ $V_{GS} = 10V$	0.8	mΩ
I_D	340	A



Ordering Information:

Ordering Code	Package Type	Marking Code	Form	Packing
AKG4N008GM-A	PDFN5X6	G4N008GM	Tape Reel	See the detail package information

Notes:

1. Contact ALKAIDSEMI sales for detail information

Maximum Ratings (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Value	Units
V _{DS}	Drain-Source Voltage	40	V
I _D	Drain Current - Continuous (T _C = 25°C) ^(Note 1)	340	A
	Drain Current - Continuous (T _C = 100°C)	240	A
I _{DM}	Drain Current - Pulsed ^(Note 2)	900	A
V _{GS}	Gate-Source Voltage	± 20	V
E _{AS}	Single Pulsed Avalanche Energy ^(Note 3)	900	mJ
P _D	Power Dissipation (T _C = 25°C)	166	W
T _J , T _{STG}	Operating and Storage Temperature Range	-55 to +175	°C

Thermal Characteristics

Symbol	Parameter	Value	Units
R _{θJC}	Thermal Resistance, Junction-to-Case, Steady-State	0.9	°C/W
R _{θJA}	Thermal Resistance, Junction-to-Ambient, Steady State ^(Note 4)	45	°C/W







Notes:







- 1. The max drain current rating is silicon limited
- 2. Repetitive Rating: Pulse width limited by maximum junction temperature
- 3. L = 0.5 mH, V_{DD} = 20 V, I_{AS} = 60 A, R_G = 25 Ω, Starting T_J = 25 °C
- 4. Mount on minimum PCB layout

Electrical Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _D = 250 μA	40			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 40 V, V _{GS} = 0 V			1	μA
		V _{DS} = 40 V, V _{GS} = 0 V, T _J = 125 °C			100	μA
I _{GSS}	Gate Leakage Current	V _{GS} = ± 20 V, V _{DS} = 0 V			± 100	nA
V _{GS(TH)}	Gate Threshold voltage	V _{DS} = V _{GS} , I _D = 250 μA	2	2.8	4	V
R _{DS(ON)}	Drain-Source on-state resistance	V _{GS} = 10 V, I _D = 20 A		0.6	0.8	mΩ
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{DS} = 20 V, V _{GS} = 0 V, F = 1 MHz		8980		pF
C _{OSS}	Output Capacitance			3560		pF
C _{RSS}	Reverse Transfer Capacitance			36		pF
R _G	Gate Resistance	F = 1 MHz		8		Ω
Switching Characteristics						
T _{D(ON)}	Turn On Delay Time	V _{DD} = 32 V , R _L = 0.65 Ω, V _{GS} = 10 V, R _G = 2.5 Ω		20		ns
T _R	Rise Time			67		ns
T _{D(OFF)}	Turn Off Delay Time			120		ns
T _F	Fall Time			78		ns
Q _G	Total Gate Charge	V _{DD} = 20 V , I _D = 50 A, V _{GS} = 10 V		110		nC
Q _{GS}	Gate-Source Charge			48		nC
Q _{GD}	Gate-Drain Charge			18		nC
Drain-Source Diode Characteristics and Maximum Ratings						
I _S	Maximum Continuous Body-Diode Forward Current				340	A
I _{SM}	Maximum Pulsed Body-Diode Forward Current				900	A
V _{SD}	Diode Forward Voltage	V _{GS} = 0 V, I _S = 50 A		0.78		V
T _{RR}	Reverse recovery time	V _{DD} = 20 V, I _D = 50 A, di/dt = 100 A/μs		103		ns
Q _{RR}	Reverse recovery charge			240		nC
I _{RRM}	Peak Reverse Recovery Current			3.5		A

Electrical Characteristics Diagrams








Figure 13: Normalized Maximum Transient Thermal Impedance






Figure 14: Maximum Forward Biased Safe Operating Area

Test Circuit and Waveform


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Revision History

Revision	Release Date	Remark
Rev.1.3	2025	

Disclaimer

The information given in this document describes the independent performance of the product, but similar performance is not guaranteed under other working conditions, and cannot be guaranteed when installed with other products or equipment. To achieve the required performance of the product in actual scenarios, the customer should conduct a complete application test to assess the functionality of the product.

Alkaidsemi assumes no responsibility for equipment failures result from using products at values that exceed the ratings, operating conditions, or other parameters listed in the product specifications.

The product described in this specification is not applicable for aerospace or other applications which requires high reliability. Customers using or selling these products for use in medical, life-saving, or life-sustaining applications do so at their own risk and agree to fully indemnify.

Due to product or technical improvements, the information described or contained herein may be changed without prior notice.